

**GP8  
SERIES 6  
PLUS**

SELF-DRIVING  
PALLET TRUCK



**SEEGRID**

216 RIDC Park West Drive  
Pittsburgh, PA 15275

US: +1 412 379 4500  
UK: 44 203 769 3119

sales@seegrid.com  
www.seegrid.com

**PRODUCT SPECIFICATIONS**

<b>Max. Capacity</b>	8,000 lbs.	<b>Safety</b>	ANSI/ITSDF/ B56.5-2012 ANSI B11.0 Primary personnel detection safety system Secondary object detection system Fork-mounted object detection system ISO 13849 category 3 emergency stop buttons LED lightbar Turn signals Acoustic warning system
<b>Max. Automatic Speed</b>	Full load 2.6 mph Unloaded 4.0 mph	<b>Standard Safety Behaviors</b>	Slows down during turns Stops if it detects an object in the primary personnel or secondary object detection systems and resumes travel once object is removed Always sounds horn before beginning or resuming automatic travel
<b>Max. Manual Speed</b>	2.3 mph	<b>Trained Behaviors</b>	Timed pauses at intersections where other traffic has right of way Wait to start until operator presses Push to Work button Sounding the horn in busy areas, near walkways, in turns, etc.
<b>Width</b>	36"		
<b>Height</b>	78"		
<b>Length with Forks</b>	91"		
<b>Weight</b>	1,540 lbs.		
<b>Wheels</b>	Rubber, Polyurethane, Vulkollan		
<b>Environment</b>	Indoor operation only Temperature: 32°F min. 104°F max. Humidity: 20-95% RH (non-condensing) Floor conditions should be free from oils, moisture, uneven/cracked flooring, and debris.		
<b>Features</b>	Flexible, infrastructure-free navigation Walk the vehicle for route training Route transfer between vehicles: train one and transfer route knowledge to all Seegrid Supervisor for connected fleet management and enterprise intelligence		
<b>Turning Radius</b>	Automatic outside min: 124" Manual outside min: 78"		
<b>Battery</b>	Battery voltage: 24V Battery max. capacity: 750 Amp x Hr Battery compartment: (LxWxH) 31"x 13"x 32" Battery connector: Standard, Red SB-175 Battery weight: 900 lbs. min. 1,500 lbs. max. Battery change roll deck: Standard		