

GT10 SERIES 6

SELF-DRIVING
TOW TRACTOR



SEEGRID

216 RIDC Park West Drive
Pittsburgh, PA 15275

US: +1 412 379 4500
UK: 44 203 769 3119

sales@seegrid.com
www.seegrid.com

PRODUCT SPECIFICATIONS

Max. Capacity	10,000 lbs.	Safety	ANSI/ITSDF/ B56.5-2012 ANSI B11.0 Primary personnel detection safety system Secondary object detection system ISO 13849 category 3 emergency stop buttons LED lightbar Turn signals Acoustic warning system Safety mat in driver's compartment
Max. Automatic Speed	Up to 4.0 mph	Standard Safety Behaviors	Stops if it detects an object in the primary personnel or secondary object detection systems and resumes travel once object is removed Always sounds horn before beginning or resuming automatic travel
Max. Manual Speed	4.3 mph	Trained Behaviors	Timed pauses at intersections where other traffic has right of way Wait to start until operator presses Push to Work button Sounding the horn in busy areas, near walkways, in turns, etc.
Width	36"		
Height	96"		
Length	60"		
Weight	1,860 lbs.		
Wheels	Rubber		
Environment	Indoor operation only Temperature: 32°F min. 104°F max. Humidity: 20-95% RH (non-condensing) Floor conditions should be free from oils, moisture, uneven/cracked flooring, and debris.		
Features	Flexible, infrastructure-free navigation Operate in manual or driverless mode Route transfer between vehicles: train one and transfer route knowledge to all Seegrid Supervisor for connected fleet management and enterprise intelligence		
Turning Radius	Automatic outside min: 96" Manual outside min: 46"		
Battery	Battery voltage: 24V Battery max. capacity: 840 Amp x Hr Battery compartment: (LxWxH) 31"x 13"x 32" Battery connector: Standard, Red SB-175 Battery weight: 854 lbs. min. 1,500 lbs. max. Battery change roll deck: Standard		